

KOMATSU

D71EX-24 / D71EXi-24 D71PX-24 / D71PXi-24 D71PX-24 WIDE / D71PXi-24 WIDE

intelligent / 2.0
MACHINE CONTROL

EPA Tier 4 Final Engine
Australia & New Zealand Specifications



Crawler dozer

Horsepower (Standard model)

Gross: 179 kW 240 HP/2100 min⁻¹
Net: 177 kW 237 HP/2100 min⁻¹

Operating weight range

D71EX-24: 22600 kg
D71PX-24: 23100 kg
D71PX-24 Wide: 23900 kg

Blade capacity (ISO 9246)

Power Angle Tilt (PAT) Dozer:
D71EX-24: 4.42 m³
D71PX-24: 4.65 m³
D71PX-24 Wide: 5.02 m³

Horsepower (iMC model)

Gross: 179 kW 240 HP/2100 min⁻¹
Net: 177 kW 237 HP/2100 min⁻¹

Operating weight range

D71EXi-24: 22700 kg
D71PXi-24: 23200 kg
D71PXi-24 Wide: 24000 kg

Blade capacity (ISO 9246)

Power Angle Tilt (PAT) Dozer:
D71EXi-24: 4.42 m³
D71PXi-24: 4.65 m³
D71PXi-24 Wide: 5.02 m³

Walk-around

Horsepower (identical for iMC model)

Gross: 179 kW 240 HP/2100 min⁻¹

Net: 177 kW 237 HP/2100 min⁻¹

Blade capacity (ISO 9246) (identical for iMC model)

PAT Dozer:

D71EX-24: 4.42 m³

D71PX-24: 4.65 m³

D71PX-24 Wide: 5.02 m³

Operating weight

D71EX-24: 22600 kg

D71PX-24: 23100 kg

D71PX-24 Wide: 23900 kg

Operating weight

D71EXi-24: 22700 kg

D71PXi-24: 23200 kg

D71PXi-24 Wide: 24000 kg





Outstanding productivity and workability

KOMPLIMENTARY MAINTENANCE

Hydrostatic Transmission (HST):

Grading and pushing applications are improved by greater control and consistent power delivery.

Powerful engine and large capacity PAT blade:

The D71EXi/PXi-24 offers the most horsepower in its class and large capacity PAT blade to increase productivity on the jobsite.



Ecology features

- NEW** • Komatsu's new emission regulations-compliant engine
- Auto idle shutdown function
- NEW** • Auto-decelerator
- NEW** • Auto E mode

Productivity and workability features

- NEW** • Great production due to engine power-up and large-capacity PAT blade
- Excellent blade visibility due to super-slant nose design
- HST control system Hydraulically-driven cooling fan
- NEW** • Additional selectable working mode H mode* (High engine idle speed mode)
*H mode is installed to only North American specification
- NEW** • PAT dozer with adjustable pitch Steering speed increase
- NEW** • Enhanced steering and working mode

Controllability features

- Palm Command Control System (PCCS)
- HST with electrical control

Working environment

- Integrated ROPS (ISO 3471) cab
- Rear view monitor system
- NEW** • Operator presence sensing system
- NEW** • Bluetooth® radio with USB port
- NEW** • LED lights

Reliability and maintenance features

- Parallel Link Undercarriage System (PLUS)
- Hydraulically-driven swing-up fan
- NEW** • Easy greasing of equaliser bar side pin
- NEW** • Easy sampling

Information and communication technology (ICT)

- Large multi-lingual high resolution Liquid Crystal Display (LCD) monitor
- Multi-monitor with troubleshooting function to minimise down time
- Energy Saving Operation Ecological operation report for assistance

Komplimentary maintenance and KOMTRAX®


Ecology features

Komatsu new engine technologies

Komatsu's New Emission Regulations-compliant Engine

U.S. EPA Tier 4 Final and EU Stage V emissions require the reduction of NOx emissions. In addition to refining the Tier 4 Interim technologies, Komatsu developed a new Selective Catalytic Reduction (SCR) device in-house.


- ① Variable Geometry Turbocharger (VGT)
- ② SCR
- ③ Komatsu Diesel Particulate Filter (KDPF)
- ④ Exhaust Gas Recirculation (EGR) Cooler



Technologies applied to new engine


Heavy-duty aftertreatment system

This new system combines a Komatsu Diesel Particulate Filter (KDPF) and Selective Catalytic Reduction (SCR). The SCR NOx reduction system injects the correct amount of Diesel Exhaust Fluid (DEF) at the proper rate, thereby decomposing NOx into non-toxic water vapour (H2O) and nitrogen gas (N2).




Heavy-duty cooled EGR system

The system recirculates a portion of exhaust gas into the air intake and lowers combustion temperatures, thereby reducing NOx emissions. Furthermore, while EGR gas flow is increased, by incorporating a high-efficiency and compactly designed cooling system, the system achieves a dynamic reduction of NOx, while helping reduce fuel consumption.



VGT system

The VGT system features Komatsu-original hydraulic technology for variable control of air-flow. The VGT supplies optimal air according to load conditions and the upgraded version features improved exhaust temperature management.




Electronic control system

The electronic control system performs high-speed processing of all signals from sensors installed in the vehicle and engine to ensure total control of the equipment under all conditions. Engine condition information is displayed via an on-board network on the monitor inside the cab, providing necessary information to the operator. Furthermore, managing the KOMTRAX helps customers use this information to engage in appropriate maintenance.



High Pressure Common Rail (HPCR) fuel injection system

The system is designed to achieve an optimal injection of high-pressure fuel by means of computerised control, thereby improving combustion efficiency and reducing Particulate Matter (PM) emissions. Equipped with the auto-decelerator, which automatically decreases the engine speed at the set time after the work equipment or travel lever is set in neutral.



Redesigned combustion chamber at top of piston

The combustion chamber at the top of the piston has a new shape designed to improve combustion and further reduce NOx, PM, fuel consumption and noise.

Komatsu Closed Crankcase Ventilation (KCCV)

The KCCV efficiency is significantly increased from previous models from around 50% efficiency to 95% efficiency.



Selectable working mode

P mode is the mode designed for powerful operation and maximum production. E mode is designed for general dozing applications providing adequate speed and power while saving energy. For CO2 reduction and energy saving, the monitor panel allows the operator to easily switch the working mode, depending on the work at hand.

P mode (Power mode)

With P mode, the engine outputs its full power, allowing the machine to perform the work requiring large production, heavy-load work, and uphill work.

E mode (Economy mode)

With E mode, the engine outputs enough power for the work without delivering unnecessary power. This mode allows for energy saving operation and is suitable for the work on a ground where the machine may cause shoe slip and the work not requiring large power such as downhill dozing, leveling and light-load work.

H mode* (High engine idle speed mode)

*H mode is installed to only North American specification.

The H mode has been added. Compared with the P mode, the engine high idle speed is higher in the H mode. This setting allows subtle changes in load to be detected, which is suitable for power-intensive work.

Auto idle shutdown function

komatsu auto idle shutdown helps reduce idle time and operating costs.

Auto-decelerator

The auto-decelerator automatically decreases the engine speed after selected period since the work equipment or travel lever return neutral.

Auto E Mode

At light load work, changing to E mode automatically to reduce fuel consumption.

Productivity and workability features

Hydrostatic transmission (HST) control system

The D71EX/PX-24 is equipped with Komatsu-designed HST provides smooth powerful turns. Fully electronic control provides full automatic shifting and enables smooth control. The travel speed can be selected smoothly with the UP/ DOWN switch, and the engine power is maximised in all speed ranges. In addition, a powerful and smooth turn is achieved by controlling the outer track faster and the inner crawler track slower.



Effective work for HST

Grading: Operator can select the optimum vehicle speed.

Pushing: Engine power can be transmitted to the tracks consistently no matter the blade load, operators don't have to select the right gear.

Side cutting: Machine can maintain consistent power to tracks when turning under a load.

Work on soft ground: HST provides smooth control of machine speed without reduction in torque.

Ground speed control: Equipped with 4 speed presets or 20 speed stepless power can be controlled without reducing engine speed.

Production improvement

Equipped with a new SAA6D114E-6 engine whose horsepower is the largest in this class. Combined with the newly designed large-capacity blade, it works high production.

Rated engine horsepower (Net)

177 kW (237 HP)

Hydraulically driven cooling fan

The engine cooling fan's speed is electronically controlled. The fan speed depends on engine coolant, oil temperatures and the fan will only rotate as fast as is necessary to adequately cool the machine's fluid. This system increases fuel efficiency, reduces the operating noise levels and requires less horsepower than a belt driven fan.

Long track-on-ground and oscillating track frame

Long track-on-ground and oscillating track frames improve machine stability and grading/dozing performance.

Steering speed increase

Speeds up the outer crawler when turning, improving maneuverability and turnability.

Enhanced steering mode

FNR shift mode: Allows operator to optimise forward and reverse shifting response speed.

Steering mode: Improved steering performance with operator adjustable turning speed.

Fast mode: Enables the outside track to speed up, while maintaining machine travel speed to improve maneuverability and turning.

Enhanced blade mode

Blade drop speed mode:

New operator adjustable blade drop response, with added quick drop feature.

Blade tilt mode:

Operator adjustable blade tilt response.

Blade lift mode:

Operator adjustable blade lift response.



PAT dozer with adjustable pitch

A power angle power tilt dozer blade with adjustable blade pitch system is available. For the D71EXi/PXi-24. The hydraulic blade tilt and angling function expands versatility and productivity in a variety of applications. The manually adjustable blade pitch further expands the versatility and productivity.



Blade capacity (ISO 9246)

5.02 m³ (PX-WIDE) | **4.65 m³** (PX) | **4.42 m³** (EX)



Super-slant nose provides excellent blade visibility

The D71EXi/PXi-24 incorporates Komatsu's super-slant nose design. Komatsu's innovative design provides excellent blade visibility for improved machine control and increased efficiency and productivity.



Controllability features




Reverse grade switches.

PCCS levers

Komatsu's ergonomically designed PCCS handles create an operating environment with complete operator control.


PCCS

The low-effort PCCS joystick controls all directional movements including machine travel speed as well as counter-rotation.



Electronic controlled hydraulic system

Electronic controlled palm commanded joystick provides precise blade control, by assistance of controller. New blade angling switch operation provides easier blade control.



Only one pedal (decelerator/brake pedal) to be operated for speed control, during operation


Machine operation becomes simple because brake function has been integrated into the decelerator pedal. Machine travel speed can be controlled using only one pedal. Character of pedal function can be changeable by mode selector switch.

Decelerator mode:

The pedal can decelerate engine revolution and vehicle travel speed. Normally can be used for all applications.

Brake mode:

The pedal can decelerate vehicle travel speed while maintaining high engine speed. This mode can be helpful to maintain work equipment, even when using the decelerates brake pedal.





Working environment

Integrated ROPS (ISO 3471) cab

The D71EXi/PXi-24's cab has an integrated ROPS (ISO 3471). High rigidity and superb sealing performance sharply reduce noise and vibration for the operator and minimise dust from entering the cab. In addition, side visibility is increased because external ROPS (ISO 3471) structure and posts are not required. Outstanding visibility has been achieved.



Comfortable ride with cab damper mounting

The D71EX/PX-24's cab mount uses a cab damper system that provides excellent shock and vibration absorption which conventional mounting systems are unable to match. The silicon oil filled cab damper mount helps to isolate the cab from the machine body, suppressing vibration and providing a quiet, comfortable operating environment.

Auxiliary input jack and two DC12 V electrical outlets

By connecting an auxiliary device to this plug input, the operator can play audio from their mobile device through the machine's sound system. Two DC12 V electrical outlets can be used as a power source for radio equipments or others.



Multifunction audio

It has functions of AM/FM radio and AUX, USB and Bluetooth® wireless technology enabled products can be connected.



Comfortable ride with new operator seat

The new operator seat has adjustable lumbar support, tilt and an electric heater. It becomes easy to adjust to the operator's shape and comfortable operation is possible in a variety of conditions. Also seat heat makes possible to work comfortably in the winter.



LED lights


LED lights are equipped on of the machine. The visibility under low light environment is improved, and work at night with ease.



Safety equipment

Rear view monitor system

On the large LCD colour monitor, the operator can view, through one camera, areas directly behind the machine. This camera can be synchronised with reverse operation.



Secondary engine shutdown switch

A new secondary switch has been added at the side of the front console to shut down the engine.



Operator presence sensing system


This feature locks out hydraulics under certain conditions to prevent unintentional movement when the operator is not in the seat.

Reliability and maintenance features

Excellent reliability and durability

Parallel Link Undercarriage System (PLUS)

Komatsu's new PLUS provides less downtime plus longer wear with up to 40% lower undercarriage maintenance costs. Rotating bushings eliminate the cost and downtime for bushing turns, and strengthened rollers and links increase wear life up to two times. With PLUS, individual links can be replaced with common track tools.




Modular design

Designed with durability in mind the machine, takes a modular approach utilising castings for strength and reduction in parts.



Self-adjusting idler support

The self-adjusting idler support provides constant and even tension on idler guide plates reducing noise and vibration and increasing undercarriage life.



Dozer frame

Steel castings reduce the number of welds, improving frame rigidity and strength.

Mainframe

High-rigidity simple hull frame structure combined with thick plates and steel castings provide increased reliability and durability.



D71EX-24/PX-24/PX-24 WIDE / D71EXi-24/PXi-24/PXi-24 WIDE

Easy maintenance

Planned maintenance is the only way to ensure long service life from your equipment. That's why Komatsu designed the D71EXi/PXi-24 with conveniently located maintenance points to make necessary inspections and maintenance quick and easy.

Hydraulically-driven swing-up fan

The D71EXi/PXi-24 utilises a swing-up fan with a gas strut-assisted lift system to provide easy access to the (Side-by-side) radiator, oil cooler and charge air cooler. The swing-up feature makes it easier to access cooling cores. The hydraulic fan has a cleaning mode where the fan rotates in the reverse direction and helps to clear off objects in front of the cooling areas.



Daily checks

All daily checks can be performed efficiently from the left side of the machine.

Easy sampling

Added sampling port for oil and coolant on machine, so you can sample very easily.



Engine oil — Coolant



Hydraulic oil —

Equaliser bar side pins

Remote grease nipple on track-frame, so you can grease equaliser bar side pins easily.



Tie-offs

Anchor points of tie-off are installed. They are used to connect the safety belts of workers for maintenance and cleaning work.



Next Generation Intelligence

Improved machine efficiency for work ranging from heavy dozing to finish grading with intelligent Machine Control technologies.

NEW **Lift layer control**

Realises consistent lift layers with automatic control.

NEW **Quick surface creation**

Makes design data by easy operation.

UPGRADE **Proactive dozing control**

Cut & carry work smooth as if performed by experienced operator.

Standard intelligent machine control

Standard factory installed integrated 3D GNSS intelligent machine control system.

No cables

No coiled cables between machine and blade.

No climbing

GNSS antenna and mast removed from blade.

No connections

No daily connections required between machine and blade.

NEW **Tilt steering control**

Relieves operator of correction operation toward target point.

NEW **Adopts two antennas supporting multiple GNSS***

Improved reliability in work accuracy due to stable receiving of satellite signals.

*Global Navigation Satellite System.

Improved machine control

Up to 8% more efficient dozer operation than comparable aftermarket machine control systems in start to finish grading tests.

Innovative

Automated blade control from rough dozing to finish grade.

Integrated

Standard factory installed machine control system.

Intelligent

New dozing mode, load control performance features.

Reliability

For higher reliability and durability

ICT* system installed as standard before shipment

*Information and Communication Technology.



**KOMPLIMENTARY
MAINTENANCE**



intelligent Machine Control




intelligent Machine Control (iMC) 2.0

D71EXi/PXi-24 utilises intelligent Machine Control 2.0 a GNSS* system that automatically controls the blade to 3-dimensional design data. Machine Control 2.0 utilises the industry's first Proactive Dozing Control logic, lift layer control, quick surface creation, and tilt steering control. A two antenna system supporting multiple GNSS which provides less down time and more work time. These added features make for improved production and efficiency.

*GNSS (Global Navigation Satellite System): General term for satellite positioning systems such as GPS, GLONASS, etc.

Quick surface creation

Designed to simplify in-field surface creation within the control box, allowing for more utilisation of iMC 2.0.



*CGI rendered image for illustration purpose only.

Tilt steering control

The blade automatically tilts under a heavy load to maintain a straight line of travel, optimising productivity throughout each pass and reducing operator fatigue.



Auto/manual switch

A conveniently located On/Off switch giving the operator control of when iMC 2.0 is active.



Function switches

Cut/fill offset switch

The target surface height can be quickly adjusted by press the offset switch (Button).



Cut/fill offset switch

Back grade mode switch


Back grade mode switch

Allows for automatic control during back grading.

D71EX-24/PX-24/PX-24 WIDE / D71EXi-24/PXi-24/PXi-24 WIDE


Lift layer control

Optimise earthwork productivity and maintain compaction quality by automatically controlling lifts to the desired heights with respect to the mapped terrain. Excess fill is eliminated as automatic blade control will follow finish surface once lifts have reached finish grade.



Proactive dozing control

Operator can utilise automatic blade control from rough grading to finish grading work. Proactive dozing control understands the terrain in the path of each cut, maximises the blade load throughout the pass, regardless of the terrain ahead, and achieves productivity similar to that of an experienced operator.




Two Antennas Supporting Multiple GNSS

Work accuracy is improved by two antennas supporting the multiple GNSS. Improvement of blade accuracy on slope Blade accuracy is maintained during slope work.



Reliability of blade accuracy

Galileo, QZSS, and BeiDou can be used in addition to GPS and GLONASS. Since the satellite capture rate is improved, the machine can be used in any time zone.



Control Box

- | | |
|---|---|
| 1 L.H. LED indicator | 5 Zoom in switch |
| 2 Upper LED indicator | 6 Zoom out switch |
| 3 R.H. LED indicator | 7 Toggle main view switch (Press: Switch the display of main window/Hold down: Adjust the brightness and sound volume) AUTO indicator Back Grade mode indicator |
| 4 Power ON/OFF and menu switch (Press: Display the main menu/Hold down: Turn ON/OFF the power supply) | |
| 1 Left window | 9 Smooth start ON/OFF |
| 2 Main window | 10 Tilt steering ON/OFF |
| 3 Lower window | 11 Toggle As-built mode change view to [none], [cut fill], [pass counts] |
| 4 Right window | 12 Quick surface creation (Create slope plane surface) |
| 5 Speed control ON/OFF | 13 Lift layer control (Create As-built design surface) |
| 6 Take a topo shot | |
| 7 Simple grading ON/OFF | |
| 8 Cut depth selection | |
| 1 Elevation control key | 7 Tilt of blade |
| 2 Slope control key | 8 Design cross-slope |
| 3 GNSS status | 9 Type of control |
| 4 Radio status | 10 AUTO indicator |
| 5 Cut/Fill offset | 11 Back Grade mode indicator |
| 6 Cut/Fill reading | 12 Lift indicator |

*This is a typical main screen of control box.



ICT

Large multi-lingual high resolution LCD monitor

A large user-friendly colour monitor provides easy to understand information for the operator. Excellent screen visibility is achieved with a high resolution LCD monitor that can easily be read at various angles and lighting conditions. Simple and easy to operate switches and function keys facilitate multi-function operations. The monitor displays data in 26 languages to globally support operators around the world.



Multi-monitor with troubleshooting function to minimise down time

Various meters, gauges and warning functions are centrally arranged on the multi-monitor. The monitor simplifies start-up inspection and promptly warns the operator with a lamp and buzzer if any abnormalities should occur.

In addition, countermeasures are indicated in 4 levels to ensure safety and help prevent the machine from having major problems. Replacement times for oil and filters are also indicated.



Energy Saving Operation

ECO guidance

In order to support efficient operation, the following four messages are displayed for fuel saving operation.



- 1) Avoid excessive engine idling
- 2) Use economy mode to save fuel
- 3) Avoid hydraulic relief pressure
- 4) Avoid over load

ECO gauge

In order to help the operator to perform in an environmentally friendly way and minimise energy consumption, an easy-to-read "ECO gauge" is displayed on the left of the multi-monitor screen.


Fuel consumption display

Average fuel consumption during the day is displayed and updated every 10 seconds.

Ecological operation report for assistance

KOMTRAX is fleet monitoring system developed by Komatsu. KOMTRAX provides machine location, actual working hours, fuel consumption, maintenance, abnormality, load frequency, and many more. Those information can be monitored through a secure web-based application. KOMTRAX also provides reports which summarize machine usage. KOMTRAX data helps to improve machine usage and make management decisions. The new D71EX/PX-24 provides the following information.

- Guidance to improve fuel consumption
- Energy saving operation report
- Working hours by working mode (P or E mode)
- Service information for U.S. EPA Tier 4 Final engine (Regeneration, failure information)
- Operator-wise working information
- Trends in use of auto idle shutdown
- Display of seat belt unfastened caution



KOMTRAX equipment monitoring

Get the whole story with



What

- KOMTRAX is Komatsu's remote equipment monitoring and management system. KOMTRAX continuously monitors and records machine health and operational data.
- Information such as fuel consumption, utilisation, and a detailed history lowering owning and operating cost.

Where

- KOMTRAX data can be accessed virtually anywhere through your computer, the web or your smart phone.
- Automatic alerts keep fleet managers up to date on the latest machine notifications.

Why

- Knowledge is power – make informed decisions to manage your fleet better.
- Knowing your idle time and fuel consumption will help maximise your machine efficiency.
- Take control of your equipment – any time, anywhere.

Who

- KOMTRAX is standard equipment on all Komatsu construction products.

When

- Know when your machines are running or idling and make decisions that will improve your fleet utilisation.
- Detailed movement records ensure you know when and where your equipment is moved.
- Up to date records allow you to know when maintenance is due and help you plan for future maintenance needs.



KOMTRAX

For construction and compact equipment.

KOMTRAX Plus

For production and mining class machines.

Specifications



Engine

Model	Komatsu SAA6D114E-6
Type	4-cycle, water-cooled, direct injection
Aspiration	Turbocharged, air-to-air aftercooled
Number of cylinders	6
Bore x stroke	114 mm x 144.5 mm
Piston displacement	8.85 L
Governor	All-speed and mid-range, electronic
Horsepower:	
SAE J1995	Gross 179 kW 240 HP
ISO 9249 / SAE J1349*	Net 177 kW 237 HP
Rated rpm	2100 min ⁻¹
Fan drive type:	Hydraulic
Lubrication system	All-speed control, electronic
Method	Gear pump, forced lubrication
Filter	Full-flow
*Net horsepower at the maximum speed of radiator cooling fan	159 kW 213 HP


U.S. EPA Tier 3 and EU Stage 3A emissions certified.

Hydrostatic transmission (hst)

Dual-path, HST provides infinite speed changes up to 11 km/h. The variable capacity travel motors allow the operator to select the optimum speed to match specific jobs. Travel control lock lever and neutral switch.

Travel speed (quick shift mode)	Forward	Reverse
1st	0–3.8 km/h	0–4.5 km/h
2nd	0–6.5 km/h	0–7.5 km/h
2.5th	0–8.4 km/h	0–9.3 km/h
3rd	0–11 km/h	0–11 km/h

Travel speed (variable mode)	Forward	Reverse
	0.8–11 km/h	0.8–11 km/h



Final drives

In-shoe mounted axial piston type travel motors with integrated two-stage planetary gear reduction. Compact in-shoe mount reduces risk of damaged by debris. Bolt-on sprocket for easy replacement.

Swing system

PCCS joystick control for all directional movements. Pushing the joystick forward results in forward machine travel, while pulling it rearward reverses the machine. Simply tilt the joystick to the left or right to make a turn. Tilting the joystick fully to the left or right activates counter-rotation. HST eliminates steering clutches and brakes, providing smooth powerful turns. Fully electronic control enables smooth control. The PCCS utilises shift buttons to increase and decrease speed.

Minimum turning radius:

D71EXi-24	3.1 m
D71PXi-24	3.1 m
D71PXi-24 Wide	3.3 m

As measured by track marks on the ground at pivot turn.

Undercarriage

Suspension	Oscillation-type with a equaliser bar and pivot shafts
Track roller frame	Monocoque, large section, durable construction
Rollers and idlers	Lubricated track rollers
Lubricated tracks	Lubricated tracks with PLUS. The track tension can be easily adjusted with grease gun.

	D71EXi-24	D71PXi-24	D71PXi-24 Wide
Number of track rollers (each side)	8	8	8
Type of shoes (standard)	Single grouser	Single grouser	Single grouser
Number of shoes (each side)	45	45	45
Grouser height	65 mm	65 mm	65 mm
Shoes width (standard)	610 mm	760 mm	915 mm
Ground contact area	39960 cm ²	49780 cm ²	59930 cm ²
Ground pressure	55.5 kPa	45.5 kPa	39.1 kPa
(with dozer, ROPS [ISO 3471] cab)	0.57 kgf/cm ²	0.46 kgf/cm ²	0.40 kgf/cm ²
Track gauge	2230 mm	2230 mm	2385 mm
Length of track on ground	3275 mm	3275 mm	3275 mm

Coolant and lubricant capacity (refill)

Coolant	54.5 L
Fuel tank	439 L
Engine oil	30.5 L
Hydraulic tank	154 L
Final drive (each side)	10 L
DEF tank	20 L

Operating weight (approximate)

Operating weight:

Including PAT dozer, ROPS (ISO 3471) cab, operator, standard equipment, rated capacity of lubricant, coolant and full fuel tank.


D71EX-24	22600 kg	D71EXi-24	22700 kg
D71PX-24	23100 kg	D71PXi-24	23200 kg
D71PX-24 Wide	23900 kg	D71PXi-24 Wide	24000 kg

Specifications

Dimensions

	D71EXi-24	D71PXi-24	D71PXi-24 wide
A	3870 mm	4010 mm (3M folding blade) 2960 mm (in transport position)	4295 mm
B	500 mm	515 mm	555 mm
C	1265 mm	1265 mm	1265 mm
D	1090 mm	1090 mm	1090 mm
E	705 mm	705 mm	705 mm
F	3275 mm	3275 mm	3275 mm
G	5810 mm	5810 mm	5810 mm
H	3170 mm	3170 mm	3170 mm
I	65 mm	65 mm	65 mm
J	2230 mm	2230 mm	2385 mm
K	610 mm	760 mm	915 mm
L	2840 mm	2990 mm	3300 mm
M	3575 mm	3705 mm	3970 mm
N	6515 mm	6540 mm	6600 mm

Ground clearance: 410 mm



Hydraulic system

Closed-centre Load Sensing System (CLSS) designed for precise and responsive control and for efficient simultaneous operation.

Hydraulic control unit:

All spool control valves externally mounted remote to the hydraulic tank. Piston-type hydraulic pump with capacity (Discharge flow) of 235 L/min at rated engine rpm.

Relief valve setting 28.8 MPa, 294 kgf/cm²

Hydraulic cylinders Double-acting, piston type

	Number of cylinders	Bore
Blade lift	2	120 mm
Blade tilt	1	130 mm
Blade angle	2	110 mm

Hydraulic oil capacity (refilling):

PAT dozer 154 L

Control valves:

3-spool control valve for PAT dozer

Positions:

Blade lift Raise, hold, lower, and float

Blade tilt Right, hold, and left

Blade angle Right, hold, and left

Additional control valve required for ripper:

Positions:

Ripper lift Raise, hold and lower

Dozer equipment

Use of high tensile strength steel in moldboard for strengthened blade construction.

	Overall length with dozer	Blade capacity (ISO 9246)	Blade width x height	Maximum lift above ground	Maximum drop below ground	Maximum tilt	Additional weight
D71EXi-24 PAT dozer	5810 mm	4.42 m ³	3870 mm x 1265 mm	1090 mm	705 mm	500 mm	0 Kg (included)
D71PXi-24 PAT dozer	5810 mm	4.65 m ³	4010 mm x 1265 mm	1090 mm	705 mm	515 mm	0 Kg (included)
D71PXi-24 wide PAT dozer	5810 mm	5.02 m ³	4295 mm x 1265 mm	1090 mm	705 mm	555 mm	0 Kg (included)



Standard equipment

- Air cleaner, double element with dust indicator
 - Air suspension seat with operator presence sensing system
 - Alternator, 24 V/90 A
 - Automatic idle shutdown system
 - Backup alarm
 - Batteries, 2 x 12 V/140 Ah
 - Blade cylinder hoses, protected
 - Cabin, integrated ROPS/FOPS design, pressurised, with viscous damper mounts
 - Closed engine hood
 - CLSS – Closed-centre Load Sensing System
 - Colour monitor, LCD
 - Combination decelerator / brake pedal
 - Cooling fan, rear, hydraulic driven with cleaning mode
 - Decelerator/brake pedal (Single pedal)
 - Diesel Exhaust Fluid dosing system (DEF)
 - EGR - Heavy duty cooled Exhaust Gas Recirculation
 - Electronic float function
 - Engine hood and side covers
 - Engine intake precleaner (Auto eject)
 - Engine shutdown secondary switch
 - EPC accumulator
 - Exhaust pipe, elbow type
 - Expansion tank
 - Factory isolation / disconnection switch
 - Final drive with planetary gear double reduction
 - Fire extinguisher 1.5kg in cabin
 - Front guard, perforated
 - Fuel prefilter with water separator
 - Fuel filtration, water separator / pre-cleaner – 10 micron; filter – 2 micron; with strainer in fuel tank fill
 - High mount foot rests
 - Hydraulically-driven cooling fan with clean mode
 - Hydraulics for ripper
 - Hydrostatic Steering System (HSS) with counter rotation
 - Hydrostatic Transmission with electric control
 - KCCV – Komatsu Closed Crankcase Ventilation
 - KDPF with curved exhaust pipe
 - KDPF – Komatsu Diesel Particulate Filter after-treatment assembly consisting of KDOC & KCSF
 - Komatsu Machine Tracking System (KOMTRAX)
 - KVGT – Komatsu Variable Geometry Turbocharger
 - Light, beacon LED & guard
 - Locks, filler caps and covers
 - Lunchbox & cup holder
 - Multi function colour monitor, 7 inch LCD
 - O-ring face seal hydraulic connectors
 - Palm Command Control System (PCCS)
 - Palm Command Electronic Controlled Blade Joystick
 - Quick shift and variable speed selection modes
 - Radiator mask, swing up
 - Radio media system BT USB
 - Radio UHF 80 channel
 - Rear view monitor system
 - Ripper assembly - Multi shank type, fixed digging angle, 3 x ripper shanks
 - SCR – Selective Catalyst Reduction assembly
 - Sealed harness connectors
 - Seat belt 78mm, retractable with caution alarm
 - Seat cover, canvas
 - Seat, air suspension type, fabric, low back, reclining with head rest
 - Self adjusting idler support with recoil spring
 - Sprocket inner guard
 - Sprockets, segmented teeth type with mud release notches
 - Starting motor, 24 V/11 kW
 - Steering system: HST system
 - Switch, turbo timer - Muirhead
 - Tie-offs
 - Track link – PLUS with heavy duty links Parallel Link Undercarriage System
 - Track roller guard, centre and end section
 - Track shoe assembly: PLUS Link
 - 610 mm single grouser shoe (EX)
 - 760 mm single grouser shoe (PX)
 - 915 mm single grouser shoe (PX Wide)
 - Underguards:
 - Oil pan and hydraulic pumps
 - ROPS cab*
 - Air conditioner (A/C)
 - AUX-injack
 - Cab accessories:
 - 12 V x 2 power supply
 - Cup holder
 - Rear view mirror
 - Front pull hook
 - LED light
 - Multifunction Audio
 - LED Work lamps (Front 4, rear 2)
- * Meets ISO 3471 ROPS standards and ISO 3449 FOPS standard.

intelligent Machine Control

- 12 month remote access to your machine [includes data & SIM]
- 12 months service level support agreement
- Auto blade on/off switch
- Dual multi-constellation GNSS antennas
- Factory integrated 3D machine control
- ICT controller
- iMC 2.0 canvas seat cover
- Komatsu chassis mounted iMU
- Komatsu GX-55 monitor
- Komatsu stroke sensors
- Lift layer control
- MC-i4 with internal 4G modem
- Network and UHF antennas
- PDC – Proactive Dozing Control
- Quick surface creation
- Receiver- UR-1 UHF and 915SS radio
- Tilt steering control

Multi-shank ripper

Weight (Including hydraulic control unit)	1900 kg
Beam length	2170 mm
Maximum lift above ground	640 mm
Maximum digging depth	580 mm



Equipment (Standard and / or Optional) complete or partial component can be changed from factory without prior notice.

Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are Komatsu's standard written warranties, which will be furnished upon request.

Komatsu and other trademarks and service marks used herein are the property of Komatsu Ltd., Komatsu Australia Pty Ltd., Komatsu America Corp., Komatsu Mining Corp., or one of their affiliates, or the respective owners or licensees.

KOMATSU

[komatsu.com.au](https://www.komatsu.com.au)

